

WS-64 B/W

2-WAY WALL MOUNTED SPEAKER

DESCRIPTIONS

Thank you for purchasing a WS-64 Wall Mounted Speaker. This user manual will provide you with useful and important information about your equipment. Please devote some time reading it and keep it at hand for future reference.

ATTENTION! Because of the continuous evolution of techniques and standards, WS-64 reserves the right to change the specifications of its products without warning. For the most updated version of this manual and general information about this and other products, please visit our website www.vl.co.th

FEATURE

- 70Hz - 20kHz Frequency response(-6db)
- 40W RMS Power
- 88dB Sensitivity
- 104dB Maximum SPL

SPECIFICATIONS

Product type	2-Way passive speaker (8Ω/100V)
Frequency response (-6dB)	70Hz - 20kHz

TRANSDUCER

Nominal coverage	80°H x 90°V
RMS Power	40W
Program power	80W(8Ω)
Nominal impedance	8Ω
Sensitivity @1w/1m	88dB
Maximum SPL calculated	104dB
Transformer taps 100V	10W, 20W, 40W
Transformer taps 70V	5W, 10W, 20W
LF Driver	6" polypropylene cone woofer
HF Driver	1.5" Silk dome tweeter

INPUT/OUTPUT SECTION

Input connector	Binding posts
-----------------	---------------

PHYSICAL SPECIFICATIONS

Cabinet/Case material	High-grade rugged polypropylene
-----------------------	---------------------------------

SIZE

Height	195mm
Width	216mm
Depth	300mm
Weight	1.26kg

