

MT-65 B/W

MULTI-PURPOSE PENDANT/WALL/GROUND SPEAKER

DESCRIPTIONS

Thank you for purchasing a VL Audio MT-65 B/W Multi-Purpose Pendant Speaker. This user manual will provide you with useful and important information about your equipment. Please devote sometime reading it and keep it at hand for future reference.

ATTENTION! Because of the continuous evolution of techniques and standards, VL Audio reserves the right to change the specifications of its products without warning. For the most updated version of this manual and general information about this and other products, please visit our website www.vl.co.th

FEATURE

- 90Hz - 20kHz Frequency response(-6db)
- 40W RMS Power
- 85dB Sensitivity
- 104dB Maximum SPL



SPECIFICATIONS

Product type	Full-range pendant speaker (8Ω/100V)
Frequency response (-6dB)	90Hz - 20kHz

TRANSDUCER

Nominal coverage	90° Conical
RMS Power	40W
Program power	80W(8Ω)
Nominal impedance	8Ω
Sensitivity @1w/1m	85dB
Maximum SPL calculated	104dB
Transformer taps 100V	5W, 10W, 20W, 40W
Transformer taps 70V	2.5W, 5W, 10W, 20W
LF Driver	6.5" polypropylene cone woofer
HF Driver	1" Silk dome tweeter

INPUT/OUTPUT SECTION

Input connector	Quick release connector
-----------------	-------------------------

PHYSICAL SPECIFICATIONS

Cabinet/Case material	Acrylonitrile butadiene styrene
IP Rating	ip66(Only with rear cover in place)

SIZE

Height	280mm
Width	208mm
Depth	208mm
Weight	3kg

